




7b Caxton House  
Broad Street  
Cambourne  
Cambridge CB23 6JN

**T** +44(0) 1954 710666  
**E** [info@epstrategies.co.uk](mailto:info@epstrategies.co.uk)  
**W** [www.epstrategies.co.uk](http://www.epstrategies.co.uk)

Registered office as above. Environmental Protection Strategies Ltd (04330320) trading as EPS.



## Appendix J – Greenfield Runoff Rates

|                |                 |
|----------------|-----------------|
| Calculated by: | Caitlin Evans   |
| Site name:     | Hemel North     |
| Site location: | Hemel Hempstead |

This is an estimation of the greenfield runoff rates that are used to meet normal best practice criteria in line with Environment Agency guidance "Rainfall runoff management for developments", SC030219 (2013), the SuDS Manual C753 (Ciria, 2015) and the non-statutory standards for SuDS (Defra, 2015). This information on greenfield runoff rates may be the basis for setting consents for the drainage of surface water runoff from sites.

## Site Details

|            |                   |
|------------|-------------------|
| Latitude:  | 51.78379° N       |
| Longitude: | 0.4332° W         |
| Reference: | 1503586862        |
| Date:      | Feb 11 2025 17:12 |

## Runoff estimation approach

FEH Statistical

## Site characteristics

|                       |   |
|-----------------------|---|
| Total site area (ha): | 1 |
|-----------------------|---|

## Methodology

|                                             |                             |
|---------------------------------------------|-----------------------------|
| Q <sub>MED</sub> estimation method:         | Calculate from BFI and SAAR |
| BFI and SPR method:                         | Specify BFI manually        |
| HOST class:                                 | N/A                         |
| BFI / BFIHOST:                              | 0.683                       |
| Q <sub>MED</sub> (l/s):                     |                             |
| Q <sub>BAR</sub> / Q <sub>MED</sub> factor: | 1.14                        |

## Hydrological characteristics

|                                | Default | Edited |
|--------------------------------|---------|--------|
| SAAR (mm):                     | 698     | 698    |
| Hydrological region:           | 6       | 6      |
| Growth curve factor 1 year:    | 0.85    | 0.85   |
| Growth curve factor 30 years:  | 2.3     | 2.3    |
| Growth curve factor 100 years: | 3.19    | 3.19   |
| Growth curve factor 200 years: | 3.74    | 3.74   |

## Notes

### (1) Is $Q_{BAR} < 2.0$ l/s/ha?

When  $Q_{BAR}$  is  $< 2.0$  l/s/ha then limiting discharge rates are set at 2.0 l/s/ha.

### (2) Are flow rates $< 5.0$ l/s?

Where flow rates are less than 5.0 l/s consent for discharge is usually set at 5.0 l/s if blockage from vegetation and other materials is possible. Lower consent flow rates may be set where the blockage risk is addressed by using appropriate drainage elements.

### (3) Is $SPR/SPRHOST \leq 0.3$ ?

Where groundwater levels are low enough the use of soakaways to avoid discharge offsite would normally be preferred for disposal of surface water runoff.

|                               |  |      |
|-------------------------------|--|------|
| <b>Q<sub>BAR</sub> (l/s):</b> |  | 1.7  |
| <b>1 in 1 year (l/s):</b>     |  | 1.44 |
| <b>1 in 30 years (l/s):</b>   |  | 3.91 |
| <b>1 in 100 year (l/s):</b>   |  | 5.42 |
| <b>1 in 200 years (l/s):</b>  |  | 6.35 |

This report was produced using the greenfield runoff tool developed by HR Wallingford and available at [www.uksuds.com](http://www.uksuds.com). The use of this tool is subject to the UK SuDS terms and conditions and licence agreement , which can both be found at [www.uksuds.com/terms-and-conditions.htm](http://www.uksuds.com/terms-and-conditions.htm). The outputs from this tool are estimates of greenfield runoff rates. The use of these results is the responsibility of the users of this tool. No liability will be accepted by HR Wallingford, the Environment Agency, CEH, Hydrosolutions or any other organisation for the use of this data in the design or operational characteristics of any drainage scheme.

## Appendix K – Drainage Strategy